

369.00 EUR  
incl. 19% VAT, plus [shipping](#)



- INTEL® Bay Trail-M N2930 SoC Processor
- 1 \* SO-DIMM slot (Max 4GB)
- 2 \* Mini PCIE slot
- 2 \* RTL8111G PCI-E Gigabit LAN
- Realtek ALC662 HD Audio CODEC with 2-Channel
- Support 1 \* 2.5" SATA Device (Max Height 9.5 mm)
- Support 1 \* m-SATA SSD Device (Mini PCI-E)
- 1 \* USB 3.0 port
- 3 \* USB 2.0/1.1 ports
- 2 \* RJ-45 ports(Gigabit LAN)

#### Motherboard Specification

|                     |                                                                                      |
|---------------------|--------------------------------------------------------------------------------------|
| CPU                 | Intel® Celeron N2930 SoC, 1.83GHz – 2.16GHz Burst, Quad-Core, 7.5W TDP/4.5W SDP      |
|                     | Intel® Celeron N2807 SoC, 1.58GHz – 2.16GHz Burst, Quad-Core, 1MB, 4.5W TDP/3.0W SDP |
| Memory              | 1 * 204-pin DDR3L-1333 SO-DIMM up to 4GB                                             |
| VGA                 | Intel HD Graphics, 313MHz - 854MHz                                                   |
| LAN                 | 2 * Realtek RTL8111G PCI-E Gigabit LAN                                               |
| Audio               | Realtek ALC662 HD Audio                                                              |
| Storage / Drive Bay | 1 * 2.5" SATA2 3Gb/s drive bay for HDD or SSD                                        |
|                     | 1 * Shared mSATA/mini-PCI Express Combo slot (Full-size)                             |

|                                  |                                                                                                                                                                                                                                                                                                                                                                          |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Wireless / Mini-PCIE Slot</b> | 1 * Mini-PCI Express slot (Half-size)<br>Wireless 802.11 b/g/n                                                                                                                                                                                                                                                                                                           |
| <b>USB</b>                       | Embedded 1 * USB 3.0 and 5 * USB 2.0                                                                                                                                                                                                                                                                                                                                     |
| <b>Form Factor</b>               | 3.5" SBC (148mm x 102mm)                                                                                                                                                                                                                                                                                                                                                 |
| <b>Chassis Specification</b>     |                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Product size</b>              | 152.6 (W) x 110 (D) x 34.8 (H) mm                                                                                                                                                                                                                                                                                                                                        |
| <b>Color</b>                     | Black                                                                                                                                                                                                                                                                                                                                                                    |
| <b>HDD</b>                       | 1 * 2.5" Hard Disk Drive Bay (Only support SATA 2.5" HDD)                                                                                                                                                                                                                                                                                                                |
| <b>Front I/O Port</b>            | 1 * Power Button<br>1 * Power LED<br>2 * HDD LED                                                                                                                                                                                                                                                                                                                         |
| <b>Rear I/O Port</b>             | 1 * USB 3.0 ports<br>3 * USB 2.0 ports<br>2 * RJ-45 ports<br>1 * DVI-I port<br>1 * SMA Connector for WiFi Antenna<br>1 * Line Out jack<br>1 * +9V ~ +24V DC-in jack                                                                                                                                                                                                      |
| <b>Other Internal Headers</b>    | These connectors may not be fully usable with chassis closed, but the information is provided for customer alternative uses.<br>1 * USB Headers for up to 2 * USB 2.0 ports<br>1 * 24-bit dual channel LVDS connector/inverter (CHRONTEL CH7511B chipset up to 1920 x 1200)<br>1 * Serial Port Header (RS232/422/485)<br>1 * 8-bit GPIO header<br>1 * AT/ATX Mode jumper |
| <b>Environment</b>               | Operating Temperature : 0 ~ 40°C<br>Storage Temperature : -20 ~ 85°C                                                                                                                                                                                                                                                                                                     |
| <b>Standard Accessory</b>        | √ 60W AC-DC Adapter x1<br>√ Power Cord x1<br>√ Wall Mount Kit<br>√ DVI-to-VGA adapter x1<br>√ DIN RAIL x2<br>√ CD Disk x1<br>√ Manual x1<br>√ WIFI antenna (with HBJC365F3AW-2930-B model)                                                                                                                                                                               |
| <b>Functional</b>                | Set Top Box, Thin Client, Car Entertainment, Smart Mini PC, POS/POI, KIOSK                                                                                                                                                                                                                                                                                               |
| <b>Packing</b>                   | Color Box Dimension: 265(W) x 100 (D) x 200 (H) mm<br>Gross Weight■1.5KG<br>Net Weight■1.3KG                                                                                                                                                                                                                                                                             |
| <b>Certificate</b>               | CE,FCC,ErP For Barebone<br>CE,FCC,TUV,UL,CCC,CB,ErP For Power Adapter                                                                                                                                                                                                                                                                                                    |