



1498.00 EUR

incl. 19% VAT, plus [shipping](#)

- Ruggedized ! IP65 !
- Intel Pentium Quad Core !
- GPS, LTE, NFC, Barcode !
- Vehicle docking optional !



Support:  [Specifications](#) |  [Product guide](#)

- 11.6" Windows Tablet with 2K Resolution
- Extra Light (<900g)
- IP65
- MIL-STD-810G on 1.2M Drop Proof, S&V, High/Low Temperature
- Hot-Swappable Battery

- 4.2 hrs Battery Life with 19.53Whr Battery
- Honeywell Software Decode Scanner 1D/2D
- WiFi ac/a/b/g/n, GPS & LTE
- NFC Module
- HW TPM 2.0 FIPS 140-2 Level 2 Compliance
- Optional docking stations (stationary or vehicle mount)

|              |                   |                                                                            |
|--------------|-------------------|----------------------------------------------------------------------------|
| DISPLAY      | Size              | 11.6" TFT-LCD                                                              |
|              | Max. Resolution   | 1920 x 1080                                                                |
|              | Luminance (cd/m2) | 500nits (Option: 300 nits)                                                 |
|              | Glass Type        | Gorilla Glass 3 and Direct Bonding                                         |
| TOUCH SCREEN | TYPE              | P-CAP                                                                      |
|              | Touch             | 10 finger capacitive multi-touchscreen supporting glove mode and rain mode |

|           |                       |                                                                                                                                                                                                                         |
|-----------|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TABLET    | Operating System      | Windows® 10 IoT Enterprise 2016 LTSC<br>Multi-Language (Option: Linux CentOS7)                                                                                                                                          |
|           | Processor             | Intel Apollo Lake Pentium N4200<br>(Quad-Cores) 1.1GHz with turbo frequency<br>to 2.5GHz, 2MB L2 Cache (4 Threads)                                                                                                      |
|           | Chipset               | Intel SoC Integrated                                                                                                                                                                                                    |
|           | System RAM            | LPDDR4 3733MHz 8GB (Option: 4GB)                                                                                                                                                                                        |
|           | System ROM            | M.2 SSD 64GB / (Option: 256GB++)                                                                                                                                                                                        |
|           | Wireless              | IEEE 802.11 ac/a/b/g/n (2.4GHz/5GHz)                                                                                                                                                                                    |
|           | Bluetooth             | BT V4.2                                                                                                                                                                                                                 |
|           | LTE/GPS               | GPS (UBX-G8020-KT)<br>LTE CAT4 Sierra Module                                                                                                                                                                            |
|           | NFC                   | NFC Reader (NXP NPC300)                                                                                                                                                                                                 |
|           | Barcode Scanner       | SW Decode: Honeywell Swift Decoder<br>(1D/2D Support)                                                                                                                                                                   |
|           | Rear Camera           | 8MP Auto-Focus CMOS built-in module with<br>Flash LED                                                                                                                                                                   |
|           | Sensor                | Ambient Light Sensor, Gyro Sensor &<br>G-sensor                                                                                                                                                                         |
|           | Ambient Light Sensor  | Yes                                                                                                                                                                                                                     |
|           | Speaker               | 2 x 0.8W                                                                                                                                                                                                                |
|           | Microphone            | Yes                                                                                                                                                                                                                     |
|           | LED Indicator         | Charging LED, Power LED                                                                                                                                                                                                 |
|           | Main Battery          | 4.2 hr, 19.53Whr Removable lithium battery<br>with latch lock (2570mAh, 7.6V)                                                                                                                                           |
|           | Hot-Swappable Battery | Yes, 2.66Whr back-up battery (700mAh*1,<br>3.8V, 1S1P)                                                                                                                                                                  |
|           | I/O Port              | 1 x USB 3.0 Type-A / 1 x Nano-SIM / 1 x<br>Audio Jack / 1 x DC Jack / 1 x POGO<br>Connector                                                                                                                             |
|           | Keypad                | 2 x Volume Key                                                                                                                                                                                                          |
|           | Fully Rugged Feature  | IP65 / MIL-STD-810G 1.5m Drop / Shock &<br>Vibration / Sand & Dust-Blowing Sand /<br>High/Low Temperature – Operation /<br>High/Low temperature – Storage /<br>Freeze/thaw –Rapid temperature change /<br>Thermal Shock |
| ACCESSORY | Dimension             | 299 x 199 x 17.7 mm (w/o bumpers &<br>hand-strap) / 307.9 x 207.9 x 29.3 mm (w/<br>bumpers & hand-strap)                                                                                                                |
|           | Weight                | 895g                                                                                                                                                                                                                    |
|           | Operating Temperature | -10°C ~ 50°C                                                                                                                                                                                                            |
|           | Storage Temperature   | -20°C ~ 60°C                                                                                                                                                                                                            |
|           | Storage Humidity      | 10% ~ 90% @40°C non-condensing                                                                                                                                                                                          |
|           | Security              | HW TPM 2.0 FIPS 140-2 Level 2<br>Compliance                                                                                                                                                                             |
|           | Certification         | CE / FCC / VCCI                                                                                                                                                                                                         |
|           | Power Adapter         | AC to DC, DC19V 65W Adaptor                                                                                                                                                                                             |
|           | Hand-strap            | Yes                                                                                                                                                                                                                     |
|           | Shoulder-strap        | Yes                                                                                                                                                                                                                     |