



0.00 EUR

incl. 19% VAT, plus [shipping](#)

- Barebone !
- Intel N97 !
- 2x LAN !
- 3 Display support !

- Powered by Intel® N97 SoC Processor (formerly Alder Lake)
- High-Performance Memory: Supports DDR5 SO-DIMM
- 4K Display: Supports DP Alt Mode
- Storage & Expansion: 1 x M.2 E-Key, 1 x M Key
- Enhanced Security: TPM 2.0
- Dual 2.5GbE Ports for Reliable and High-Speed Networking Connections

SYSTEM

MB FORM FACTOR

CPU

CHIPSET

MEMORY

BIOS

WAKE ON LAN

WATCHDOG TIMER

SECURITY

RTC BATTERY

OS SUPPORT

POWER

POWER REQUIREMENT

POWER ON MODE

DISPLAY

GPU

NUC

Onboard Intel® Processor N97 (Formerly Alder Lake-N, TDP 12W)

Intel® SoC

1 x DDR5 4800MHz, Single Channel SO-DIMM, up to 32GB

UEFI

Yes

255 Levels

TPM2.0 (dTPM, Optional)

Lithium Battery

Windows® 11 (64bit)

Windows® 10 (64bit)

Linux

DC-in 12-19V

60W Adapter: AC90~240V, DC12V/5.0A

AT / ATX (Default) Mode

Intel® UHD Graphics

	2 x Type C DP1.4 (Max Resolution: 4096 x 2160@60Hz)
DP/HDMI	1 x DP1.4 (Max Resolution: 4096 x 2160@60Hz)
	1 x HDMI 2.0 (Max Resolution: 4096 x 2160@60Hz)
	Support 3 Displays
AUDIO	
CODEC	Realtek Audio Codec
LAN	
ETHERNET	2 x RJ45 for Intel® I226-V 2.5GbE
SYSTEM I/O	
	2 x RJ45
	1 x HDMI 2.0
	1 x DP 1.4
REAR PANEL I/O	2 x USB 3.2 Gen 2
	1 x DC-in (Lockable)
	2 x WIFI Antenna Holes (Optional)
	1 x GND Hold
	1 x Power Button
FRONT PANEL I/O	2 x USB 3.2 Type C support DP ALT mode
	1 x Combo Audio (Line out & Mic)
	1 x RS-232/422/485
EXPANSION	
M.2	1 x M-Key 2260/2280 (PCIe 3.0 x2/SATA III) Support NVMe
	1 x E-Key 2230 (USB 2.0/PCIe 3.0 x1) Support CNVio
MECHANICAL	
MOUNTING	Wall + VESA mount
DIMENSIONS (W x D x H)	129.0 (W) x 109.4 (D) x 34.0 (H) mm
NET WEIGHT	0.56 KG
ENVIRONMENT & CERTIFICATION	
OPERATING TEMPERATURE	-20°C ~ 60°C (-4°F ~ 140°F)
CERTIFICATION	CE/FCC Class A
	LVD
	China RoHS
	CMRT Report
ESG DECLARATION	TSCA Declaration
	WEEE
	REACH